

2-00457R00-600940010-4

~~SECRET~~  
CENTRAL INTELLIGENCE AGENCY  
~~CONFIDENTIAL~~

-2-

Item (Figures in tons)	Total Needed	Expected Production			Difference
		German	SAG	Total	
Industrial oil	40,050	18,420	15,540	33,960	6,090
Automobile oil	16,328	7,050	8,600	15,650	678
Industrial fat	4,500	4,500	-	4,500	-
Vaseline	510	510	-	510	-
<b>Total</b>	<b>61,388</b>	<b>30,480</b>	<b>24,140</b>	<b>54,620</b>	<b>6,768</b>

It is anticipated that 75,000 tons of crude oil will be processed, and this amount could be increased to 90,000 tons.

3. To compensate for the deficits in the total amount, the following emergency measures were proposed:
  - a. Regular delivery of 10,000 tons of crude oil monthly from Austria.
  - b. Preparation of 15 heated tank car trains for crude oil transport (at present 10 trains, partly heated).
  - c. Creation of a crude oil reserve by winter in case of interruption of transport.
  - d. Immediate negotiations for contracts for delivery of crude oil from Romania, Hungary, and Poland in case Austria cannot guarantee the amount of crude oil required.
  - e. Immediate release of 1440 tons of iron and steel supplies (remainder) for procurement of apparatus and spare parts (boiling tubes, boilers, condensor tubes, compressors, etc.) for carrying out of urgent repairs and for reconstruction.
  - f. Guarantee of the requirements requested for petroleum processing works and hydrogenation plants in essential auxiliary materials, such as:
    - 3,600 tons pure propane from Schwarzheide and Böhlen
    - 270 tons phenol from Leuna
    - 90 tons butanol from Schkopau
    - 2,100 tons sulphuric acid
    - 1,155 tons fuller's earth from Stassfurt (600 tons paraflor from Oppau for the period 1 April to 31 December 1948)
  - g. Agreement with the main administration of the SAGs not to let the production of lubricating oil for the period from 1 April to 31 December 1948 fall below 20,000 tons at Tröglitz and 5,000 tons at Schkopau.
  - h. Importation of special oil currently non-produceable, such as hot steam cylinder oil with flash point above 310° C or high pressure compressor oil, paraffinum liquidum "nach DAB 6."

~~SECRET~~

~~SECRET~~